

Z-Drape Panel

SOFT



The unique Z-Drape Panel is a true trailblazer in the field, going where no other product can compete in compactness, ease of setup, and value. Imagine a 30-ft x 20-ft video wall fitting in a minivan! Standard 3 meter x 3 meter panels give rental shops a variety of winning combinations. Customs sizes are also made to order.

Lightweight and easy to set up and load out, the Z-Drape Panel eases the demands of rigorous touring.



*All photos on this page show a 37.5mm panel.

Specification	Z-Drape Panel 25	Z-Drape Panel 37.5	Z-Drape Panel 50	Z-Drape Panel 75
Pitch	25mm	37.5mm	50mm	75mm
Brightness (Nit or cd/m ²)(Max.)		1,420	430	178
Resolution H x V		80x80	64x64	40x48
Pixels / Module	128	128	128	128
Pixels / m ²	1,600	711	400	177
Module Size (cm) V x H x D	.2m x .4m	0.3m x 0.6m	0.4m x 0.8m	0.6m x 1.2m
Module Size (ft) V x H x D	.66' x 1.31'	.98' x 1.97'	1.31' x 2.62'	1.97' x 3.94'
Module Area (m ²)		0.18	0.32	0.72
Panel Size (cm) V x H x D		3m x 3m	3.2mx3.2m	3mx3.6m
Panel Size (ft) V x H x D		9.92' x 9.92'		
Panel Area (m ²)		9	10.24	10.80
Refresh rate (Hz)		1,000	1,000	1,000
View Angle H x V		120°x120°	120°x120°	120°x120°
Power / m ² (W) (max/avg)		40		
Panel Voltage	5VDC	5VDC	5VDC	5VDC
LED type	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD
Protection Level (front/rear)	IP44	IP44	IP44	IP44
Operating Temp (C)	-10° – 50°	-10° – 50°	-10° – 50°	-10° – 50°
Operating Humidity	10%–90%	10%–90%	10%–90%	10%–90%
Weight m ²		5.0kg/	3.2kg/m ²	2.8kg/m ²
Colors	16.7million	16.7million	16.7million	16.7million
Driver Mode	Constant Current	Constant Current	Constant Current	Constant Current
Voltage	90-260 VAC	90-260VAC	90-260VAC	90-260VAC